

# BK Precision Clamp Meter

Part No. 01DCM330

Back to [Clamp Meter](#) Main Page

Specifications	model 330B
AC Current (using Clamp)	
Ranges	200A, 1000A
Resolution	100mA, 1A
Accuracy (50-60 Hz)	+-(1.5% rdg + 5D)
Overload Protection	1200A
<b>DC Current (using Clamp)</b>	
Range	Does not apply
Resolution	
Accuracy	
Overload Protection	
<b>AC Voltage (using test leads)</b>	
Range	750V
Resolution	1V
Basic Accuracy	+-(1.2% rdg + 5D)
Overload Protection	1000V DC /750V RMS
Input Impedance	4.5 M $\Omega$
<b>DC Voltage (using test leads)</b>	
Range	1000V
Resolution	1V
Basic Accuracy	+-(0.5% rdg + 1D)
Overload Protection	1000V DC/750V RMS
Input Impedance	10 M $\Omega$
Resistance	
Range	200 $\Omega$ , 20kOhm, 20 MOhm, 2000MOhm
Resolution	0.1 $\Omega$ , 10Ohm, 10kOhm, 100kOhm
Basic Accuracy	+-(1% rdg + 3D) 4k $\Omega$ -4MOhm: +-(1% rdg + 3D) 40M $\Omega$ : +- (3% rdg + 3D)
Overload Protection	500V DC/AC RMS
Frequency	
Range	Does not apply
Resolution	
Accuracy	

Overload Protection	
Capacitance	
Range	Does not apply
Resolution	
Accuracy	
Overload Protection	
Jaw Opening	2.24" (57mm)
Display	3 3/4 digit LCD 2000 count
Polarity	
Measure Rate	2.5/sec.
Overrange Indication	"OL"
Operating Temperature	32 ° ~ 122 ° F, 70% RH (0 ° - 50 ° C)
Storage Temperature	-4 ° - + 140 ° F, 80% RH (-20 ° - +60 °C)
Power Requirements	
Battery Life	500 Hours
Dimensions	10.8x3.6x1.7" (275x90x43 mm)
Weight	17 oz. (482g)
<b>One Year Warranty</b>	
<b>Accessories</b>	
SUPPLIED: Battery, Test leads, Instruction Manual, Carrying Case OPTIONAL: TL-2A Deluxe Test Leads, TL-3 Accessory Tlp Kit (for TL-2A), TL-130A General Purpose DMM Kit, PR-28A High Voltage Probe, CP-3 AC/DC Current Clamp Adapter, LC-33 Carrying Case	