

Instek Function Generator Model GFG-8215A

Part No. 01GFG8215

Back to [Function Generator](#) Main Page

FEATURES

- * Frequency Range: 0.3Hz ~ 3MHz
- * Waveforms: Sine, Triangle, Square, Ramp, TTL and CMOS Output
- * External Voltage Controlled Frequency (VCF) Function
- * Duty Cycle Control with Signal Inversion Capability
- * Variable DC Offset Control
- * Two-Step (-20dBx2) and Variable Attenuator
- * Built-In 6 Digit Counter with INT/EXT Function Up to 150MHz / High Resolution(GFG-8216A)

SPECIFICATIONS

MAIN	
Frequency Range	0.3Hz ~ 3MHz (7 Range)
Amplitude	> 10Vpp (into 50Ω load)
Impedance	50Ω ±10%
Attenuator	-20dB ± 1dBx2
DC Offset	<-5V ~ >5V (into 50Ω load)
Duty Control	80% : 20% : 80% to 1MHz Continue variable
Display	6 digit LED display
	*GFG-8215A does not have display.
Range Accuracy	± 5%+1Hz (at 3 position) for GFG-8215A
SINE WAVE	
Distortion	≤ 1%, 0.3Hz ~ 200kHz
Flatness	< 0.3dB, 0.3Hz ~ 300kHz < 0.5dB, 300kHz ~ 3MHz
TRIANGLE WAVE	
Linear	≥ 98%, 0.3Hz ~ 100kHz ≥ 95%, 100kHz ~ 3MHz
SQUARE WAVE	
Symmetry	± 2%, 0.3Hz ~ 100kHz
Rise or Fall Time	≤ 100nS at maximum output (into 50Ω load)
CMOS OUTPUT	
Level	4Vpp ±1Vpp ~ 14.5Vpp±0.5Vpp adjustable
Rise or Fall Time	≤ 120nS
TTL OUTPUT	
Level	≥ 3Vpp
Fan Out	20 TTL load
Rise or Fall Time	≤ 25nS
VCF	
Input Voltage	0V ~ 10V ±1V (100 : 1)
Input Impedance	10kΩ ± 10%

POWER SOURCE

AC115V/230V ± 15%, 50/60Hz

ACCESSORIES

Instruction manual x 1, Power cord x 1, GTL-101 x 2;
GTL-101x1 for GFG-8215A

DIMENSIONS & WEIGHT

251(W) x 91(H) x 291(D)mm, Approx. 2.1kg