

# BK Precision Capacitance Meter

## Model 890B

Back to [890B Main Page](#)

Specifications	model 890B
<b>CAPACITANCE</b>	
RANGE (Best Resolution)	1000pF (0.1 pF) 10nF (1 pF) 100nF (10 pF) 1000nF (0.1nF) 10uF (1nF) 100uF (10nF) 1000uF (0.1uF) 10mF (1uF) 50mF (10uF)
ACCURACY	+-(1% rdg + 11 dgt) +-(1% rdg + 6 dgt) +-(0.5% rdg + 4 dgt) +-(0.5% rdg + 4 dgt) +-(0.5% rdg + 4 dgt) +-(0.5% rdg + 4 dgt) +-(0.5% rdg + 4 dgt) +-(0.5% rdg + 4 dgt) +-(1% rdg + 6 dgt) +-(2% rdg + 6 dgt)
<b>POWER SOURCE</b>	
	9V Battery
BATTERY LIFE	80 hours typ. (alkaline, no back light)
DISPLAY	4 ½ digit LCD (dual)
DISPLAY COUNT	11,000
OPERATING TEMPERATURE	32 <sup>0</sup> to 122 <sup>0</sup> F (0 <sup>0</sup> to 50 <sup>0</sup> C)
STORAGE TEMPERATURE	-4 <sup>0</sup> to 140 <sup>0</sup> F (-20 <sup>0</sup> to 60 <sup>0</sup> C)
DIMENSIONS (LxWxH)	7.24x3.42x1.61" (184x87x41 mm)
WEIGHT	11.3 oz. (320g) approximate
<b>Three Year Warranty</b>	
<b>Accessories</b>	
SUPPLIED: Test Leads, Manual, Battery	
OPTIONAL: TL-8 SMD Probe AK-890 RS-232	
CARRYING CASE: (Not included) LC-29B	